



**SP50 Push Rod Camera**  
**SP50 Auto Uprighting Colour Camera**

- 42 mm diameter stainless steel waterproof body (tested to 6 bar pressure)
- Heavy duty stainless steel coiled spring
- 1/4 inch inter-line type colour CCD image sensor
- Effective pixels 500 Horizontal x 582 Vertical
- Horizontal resolution more than 350 TV lines
- Auto white balance
- Electronic Iris
- Lens 3.6 mm F2.0 focal length 6" inches to infinity
- Operating temperature -5°C to 45°C max
- Illumination 18 bright white LEDs

**SP50 Coiler**

- Powder coated steel coiler frame in Hi viz site safety colour
- Electronic hub counter encoder
- Integral slipping with stainless steel bearing
- Detachable coupling to remove camera from rod
- 60 meters of durable GRP reinforced 10.5 mm diameter semi rigid rod
- Compatible with all SP and most other reputable manufacturers control units

Length: 700 mm  
 Width: 360 mm  
 Height: 725 mm  
 Weight: 20 Kg

Camera Centering  
 Skid Options



Low friction skid for  
 100 mm diameter pipes



Low friction skid for  
 150 mm diameter pipes



Brush skid for  
 100 mm diameter pipes



Brush skid for  
 150 mm diameter pipes