


### **SP75 Mini Cam Crawler**

For use in 100 mm through to 225 mm diameter pipes


- Manufactured from CZ121 solid brass with stainless steel fittings
- Crawler specification:
  - Length: 340 mm    Height: 75 mm
  - Width: 75 mm    Weight: 7 kg (without wheels)
- Powerful 48 volt DC motor with variable forward and reverse speed control
- Planetary 100:1 ratio gearbox
- Crown wheel and Pinion 1:1.5 ratio drive gear with 8 mm pitch drive chain
- Robust waterproof 19 way military type rear connector
- Fully waterproof with double quad axle seals (Pressure tested to 50 psi)
- **Integral Colour Camera Pal or NTSC**
- 1/4" inch inter-line type colour CCD image sensor
- Effective pixels 500 horizontal x 582 vertical
- Horizontal resolution more than 350 TV lines
- Electronic iris with auto white balance
- Lens 3.6 mm F2.0 focal length 6" to infinity
- Operating temperature -5°C to 45°C max
- **Integral Twin LED lights**
- Luxeon enhanced white LEDs O-ring sealed behind toughened glass
- View angle 10 degrees
- Colour temperature 5500K
- Luminous flux 18 lumens



SP-225 Aluminium Wheel



SP-15 Stainless Steel Wheel



SP-10 Rubber Compound Wheel

[www.amindustrial.co.uk](http://www.amindustrial.co.uk)

[info@amindustrial.co.uk](mailto:info@amindustrial.co.uk)

*Southern Office*  
**AM Industrial (UK) Ltd,**  
 Unit 13 Nimbus,  
 Hercules Way,  
 Farnborough,  
 Hants., GU14 6UU

Tel: +44 (0) 1252 544 800  
 Fax: +44 (0) 1252 545 296

*Northern Office*  
**AM Industrial (UK) Ltd**  
 Unit 7 Woodrow Business Centre,  
 4 Woodrow Way,  
 Irlam, Manchester,  
 M44 6NN

Tel: +44 (0) 161 775 8555  
 Fax: +44 (0) 161 775 8555